

PowerBoss Phoenix 28 / 32XL

Walk-Behind Scrubber

With one chassis and two interchangeable scrub decks to select from. The Phoenix 28 / 32 XL automatic scrubber provides two model choices in one machine. Adaptable to meet your cleaning needs, the Phoenix 28 / 32 XL is available with interchangeable scrub decks in 32" coverage, disc or cylindrical and optional accessories.

Constructed of a steel frame and rotationally molded polyethylene tanks and bumpers, the Phoenix 28 / 32 XL is built to last. It is ergonomically designed for operator comfort and ease-of-use with one button scrub-smart control and an excellent line of sight due to its low profile. With outstanding maneuverability and standard large pneumatic studded tires, the Phoenix 32 can make effortless turns on its own axis while recovering all dispensed water.

The Phoenix 28 / 32 XL is equipped with a "belly bar" that prevents the operator from being pinned behind the machine when in reverse mode. Also standard, is a color coded LED battery gauge that will let the operator know if any error code faults are coming from the on-board computer. This helps pinpoint any problem for quick and easy repair.

The LED battery gauge also acts as an error code indicator. The error code can help speed up repairs by pinpointing a technical problem and minimizing troubleshooting time.



Specifications

Scrub Path:	32"
Squeegee Width:	47"
Coverage Performance:	33,500 ft ² / hr
Scrub Brush (Disc):	Disc: two (2) 16"
Scrub Brush (Cylindrical):	Cylindrical: two (2) 31 – ¼ offset
Brush Motor and RPM (Disc):	1.5 HP dual right angle 300 rpm
Brush Motor and RPM (Cylindrical):	Two (2) 1 HP 900 rpm
Brush Pressure:	Two (2) settings: regular and heavy
Solution Tank:	31 gallons
Recovery Tank:	35 gallons
Tank Construction:	Polyethylene
Dimensions:	L x W x H: 66" x 38" x 46"
Drive System:	½ HP transaxle
Vacuum:	¾ HP 3-stage tangential bypass
Pump:	60 psi
Wheels:	Two (2) 12" pneumatic, two (2) 5" casters
Frame:	11 gauge steel
Controls:	5-mode selector, speed control, solution control, directional
Brush Lifting Mechanism:	Actuator
Battery Pack:	Six (6) 6-volt, 275 ah
Transport Speed:	230 feet / minute
Weight:	1,030 lbs
Charger:	36V, 20 amp, 120 vac / 230 vac
Options:	Wheels: 12" foam-filled or 12" soft ride solid; off-aisle wand; Linatex squeegee; spring loaded casters

General Description:

- Cleans 33,500 ft² per hour
- 32" cleaning path
- Two (2) 31.25" cylindrical brushes or two (2) 16" disc brushes
- Two (2) 1 HP 900 rpm brush motors
- 31 gallon solution tank
- 35 gallon recovery tank
- Working speed 3 mph
- battery powered
- ¾ HP 3-stage vacuum motor
- Front: two (2) 12" pneumatic wheels; Rear: two (2) 5" caster wheels
- Two (2) brush pressure settings
- 11 gauge steel frame
- Weight: 1,030 lbs with batteries
- W x L x H: 34" x 66" x 46"